SEALED-BLOK™

TRUSTED. DURABLE. RELIABLE.

SRL WITH FIELD PROVEN TECHNOLOGY, RSQ™ FEATURE & RETRIEVAL CAPABILITIES

THE ULTIMATE IN FALL PROTECTION

DBI SALA®

SEALED-BLOK™

CONTENTS

Product Overview 2

Typical Applications & Markets 2

Features & Benefits 3

Choose Your Mode 4

Assisted Rescue Options 'Engage' The Descent Mode 4

Confined Space? No Problem 5

Range Overview 6

Options & Accessories 7

Why Choose Capital Safety? 8

For more information about our range of equipment visit our website at **www.capitalsafety.com**

PRODUCT OVERVIEW

TRUSTED

DBI-SALA® continues to set the standard for quality in fall protection. The DBI-SALA® Sealed-Blok™ family has the most comprehensive line of sealed SRLs in the industry and decades of proven field service. **The best just got better...**

DURABLE

- Stands up to the harshest environments
- Heavy-duty design
  - Corrosion resistant
  - Stainless steel end-plates
  - Aluminum housing

RELIABLE

- Dynamic components sealed inside the housing (IP68 rated).
  - Protects from particles entering product
  - Protected against complete or continuous submersion in water
- Decades of service
- Field proven in the world's toughest environments
- Design extends maintenance intervals and product longevity

TYPICAL APPLICATIONS

Offshore platform access

Confined space

Saltwater environments

Dirty environments

TYPICAL MARKETS

Oil and Gas

Off-Shore Wind Energy

Mining

Marina

Utilities

Waste water treatment

Municipalities

FEATURES & BENEFITS



ANTI-RATCHETING DESIGN

Stays locked on rigid and non-rigid (horizontal lifeline) anchors

NEW SEALED DESIGN (Patent Pending)

Ensures efficient, safe operation under all working conditions — the only SRL to meet IP68 sealed rating

140KG WEIGHT CAPACITY

Higher capacity for operator and tools

CARRYING HANDLE

Built-in design for easy transport with improved ergonomics

SECONDARY ANCHORAGE POINT

Certified for "dropped objects" protection Rated for fall arrest if primary anchor fails

RETRIEVAL WINCH

RSQ™ DUAL MODE DESIGN

Allows user to select between fall arrest mode and descent mode

5MM DIAMETER WIRE ROPE

Stainless steel for corrosion resistance

SELF-LOCKING SWIVEL HOOK

Limits lifeline twisting

360LB GATE

Reduces chances of accidental disengagement ("roll-out")

IMPACT INDICATOR

Provides visual indication of Fall Arrest

PIVOTING ANCHORAGE LOOP

Centres the load

ALUMINUM HOUSING

Provides exceptional strength, durability and corrosion resistance

STAINLESS STEEL END-PLATE

Durable construction for harsh environments

TRIPOD/DAVIT ARM BRACKET

No tools required for install

ERGONOMIC CABLE HANDLE

Provides added comfort and ease-of-use when making connections

iSAFE™

INTELLIGENT SAFETY SYSTEM

Track inspection, control inventory and manage information

GALVANISED AND STAINLESS STEEL CABLE

Abrasion resistant and corrosion resistant lifeline options

FAST-LINE™

Provides the user with ability to replace the lifeline in the field

WORLD'S FIRST DUAL-MODE SELF-RETRACTING LIFELINE FALL ARREST AND RESCUE

Exclusive design provides both fall arrest with assisted rescue capabilities and automatic self rescue for ultimate versatility.

- Built-in Rescue Device becomes an integral part of a Rescue Plan
- Standard fall arrest mode
- Automatic rescue mode
- Remote/Assisted activation

CHOOSE YOUR MODE

Fall Arrest Mode/Assisted Rescue

A speed sensing brake stops the fall, reduces forces imposed on the user to safe levels of 6kN or less and allows for assisted rescue to take place.

Automatic Rescue Mode/ Self Rescue Descent

A speed sensing brake slows the fall, then instantly a centrifugal brake activates, lowering the user at a controlled speed to the next level or ground.

ASSISTED RESCUE OPTIONS 'ENGAGE' THE DESCENT MODE

Traditional assisted rescue operations may also be conducted.

CONFINED SPACE? NO PROBLEM

The mechanical device is one of the most critical parts of a rescue system. It provides the means to retrieve an incapacitated worker to safety. Lifeline type and length are just a few of the options. A 3-way retrieval SRL can be used as either a primary or secondary device depending upon your application.

3-WAY RETRIEVAL SRL'S

FEATURES:

- Raise and lower personnel
- Simple change in/out of Retrieval
- Stow away handle
- Optional bracket for davit attachment
- Available with RSQ™ Option
- For rescue use only

FAST-LINE™ FIELD REPLACEABLE LIFELINE MODELS

FEATURES:

- Provides trained End-Users with the ability to replace lifeline
- SRL will not operate if rebuilt improperly
- No need to break seal to replace lifeline
- Lowers overall cost of ownership

TRUSTED IN THE FIELD

Safety engineers and site directors trust DBI-SALA® for the type of high quality, rugged systems that will ensure top performance when it is needed the most. Our systems meet applicable industry standards. We also customize solutions to suit customer needs.

3-way models with built-in emergency retrieval and mounting brackets are ideal for confined space rescue.

Available with and without mounting brackets.

SEALED-BLOK™ RANGE OVERVIEW

Lifeline Material	Snap Hook Material	Retrieval Capability	RSQ™ Capability	140kg Weight Capacity	4.5m	9m	15m	25m	40m	53m
Galvanised Cable (5mm)	Steel			✓	3400828	3400803	3400950	3400866	3400971	3400656
			✓	✓				3400891		
		✓		✓		3400854	3400955	3400880		
		✓	✓	✓				3400916		
Stainless Steel Cable (5mm)	Stainless Steel			✓	3400830	3400805	3400951	3400867	3400972	3400658
			✓	✓			3400961	3400892		
		✓		✓		3400856	3400956	3400881	3400986	
		✓	✓	✓			3400944	3400917		
Weight					5.5kg	9kg	14.5kg	20kg	27kg	56.5kg
Housing Material					Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Approximate Length					25cm	29cm	34cm	39cm	43cm	43cm
Approximate Width					19cm	24cm	27cm	30cm	35cm	35cm
Approximate Height					11cm	14cm	18cm	18cm	20cm	31cm
Retrieval Models						✓	✓	✓	✓	
RSQ™ Model							✓	✓	✓	
Fast-Line™ Field Replaceable Lifeline							✓	✓	✓	✓
140 kg Capacity					✓	✓	✓	✓	✓	✓
Meets IP68					✓	✓	✓	✓	✓	✓
Carrying Handle					✓	✓	✓	✓	✓	✓
Pivoting Anchorage Loop					✓	✓	✓	✓	✓	✓
i-Safe™					✓	✓	✓	✓	✓	✓
Tripod/Davit Arm Bracket (Optional)						✓	✓	✓	✓	
Ladder Bracket (Optional)					✓	✓	✓	✓	✓	✓
Snap Hook (Patented)					✓	✓	✓	✓	✓	✓
- 1633 kg Rated Gate					✓	✓	✓	✓	✓	✓
- Self-Locking Gate					✓	✓	✓	✓	✓	✓
- Swiveling Hook					✓	✓	✓	✓	✓	✓
- Impact Indicator on Hook					✓	✓	✓	✓	✓	✓
- ANSI Z359.1/ Z359.12 Compliant					✓	✓	✓	✓	✓	✓
5mm Diameter Wire Rope					✓	✓	✓	✓	✓	✓
Aluminum Housing					✓	✓	✓	✓	✓	✓
Stainless Steel End-Plate					✓	✓	✓	✓	✓	✓

OPTIONS & ACCESSORIES

FIRST-MAN-UP™ POLE
(2.4-4.8m) with Assisted Rescue Tool

	kg
3500202	3.00

REPAIR TOOL

	kg
9600037	0.50

MOUNTING BRACKET
for 9m, 15m, 25m and 40m Sealed-Blok™

	kg
3401025	0.30

ASSISTED RESCUE TOOL ONLY
If you already have a First-Man-Up™ Pole

	kg
3500200	0.50

SAFLOK™ STEEL CARABINER
Self Locking/Closing, 19mm Gate Opening

	kg
2000112	0.25

SAFLOK™ STEEL CARABINER
Self Locking/Closing, 30mm Gate Opening

	kg
2000113	0.60

SAFLOK™ STEEL CARABINER
Self Locking/Closing, 50mm Gate Opening

	kg
2000114	0.66

CABLE REPLACEMENT ASSEMBLY FOR FAST-LINE™

	15m	25m	40m	53m
Stainless steel cable with stainless steel hook	3900107	3900111	3900114	3900170
Galvanised cable with plated hook	3900105	3900108	3900112	3900168

capital
SAFETY

GLOBAL LEADER IN FALL PROTECTION

Capital Safety is the Global leader in fall protection equipment, systems and anchors.

Capital Safety est le leader mondial en matière d'équipement, de systèmes et d'ancrages de protections antichute.

Capital Safety ist weltweit führend auf dem Gebiet von Absturzsicherungsausrüstung, -systemen und Anschlagmöglichkeiten.

Capital Safety es el líder mundial en equipos, sistemas y anclajes de protección contra caídas.

Capital Safety is wereldleider in valbeveiligingsapparatuur, -systemen en verankeringen.

Capital Safety è leader globale nell'anticaduta per dispositivi di protezione individuale, sistemi e ancoraggi.

Capital Safety är globala inom utrustning, system och förankringar för fallskydd.

EUROPE, MIDDLE EAST & AFRICA

FRANCE
Le broc Center, Z.I. 1re Avenue – BP15
06511 Carros Le Broc Cedex, FRANCE
t: +33 (0) 4 97 10 00 10
f: +33 (0) 4 93 08 79 70

UK
5a Merse Road, North Moons Moat
Redditch, B98 9HL, UK
t: +44 (0) 1527 548 000
f: +44 (0) 1527 591 000

GERMANY
Hagener Strasse 44, D-57489,
Drolshagen, GERMANY
t: +49 (0) 2 76 18 33 82 29
f: +40 (0) 2 76 18 33 81 93

DUBAI
ME Branch Office, PO Box 17769
JAZFA, DUBAI – UAE
t: +971 (4) 88 11 4 66
f: +971 (4) 88 11 4 67

CUSTOMER SERVICES

00 800 999 55500 **information@capitalsafety.com** **capitalsafety.com**

DBI SALA®

All rights reserved. The material contained herein is copyrighted; no part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise without prior written permission from Capital Safety.